

PLAN N.T.S.

NOTES

- DIMENSIONS TO BE SAME FOR ALL SIZES OR TYPES OF OPENINGS.
- 2. CONCRETE MAY BE DELETED ON ROAD MIX STREETS UPON APPROVAL OF INSPECTOR.
- 3. CONCRETE TO BE CLASS "A" (SIX SACK).
- 4. CONCRETE TO BE BARRICADED FOR THREE DAYS AFTER POURING.
- CONCRETE CURE TO BE IN ACCORDANCE WITH SECTION 90-7 "CURING CONCRETE" OF THE STANDARD SPECIFICATIONS PER COUNTY/CITY MOST CURRENT EDITION.
- 6. USE OLDCASTLE/CHRISTY BOXES AND LIDS AS FOLLOWS:

3/4" SERVICE B12 BOX W/B12D LID

1" SERVICE B16 BOX W/B16D LID

1-1/2" - 2" SERVICE B36 BOX W/B36E LID

3" - 4" SERVICE B48 BOX W/B48 M2 LID

- SEND RFI TO OMWC FOR LARGER OR MULTIPLE APPLICATIONS.
- ALL BOXES & LIDS SHALL BE PURPLE OMWC APPROVED COLOR AND MARKED "IRRIGATION".

EXISTING SURFACE
SURFACING

VALVE BOX
SEE NOTE 6

ELEVATION

N.T.S.

REV. DATE: 2/18/19

OILDALE MUTUAL WATER CO

NON-POTABLE/IRRIGATION METER BOX IN LANDSCAPE AREA

DATE: 8/1/13

PLATE No. IRR-120